



# PS753

## 4K Desktop Document Camera



A 4K document camera with 300x zoom, HDMI, VGA, USB, and IP streaming.

Lumens® PS753 is a 300x zoom desktop document camera with a professional Sony imaging sensor. It delivers vivid colors and detailed pictures whether it is reproducing a document or a 3D object. The PS753 is easy to connect to computers, displays, and networks, with HDMI, VGA, USB, and IP outputs. It is designed for use in lecture halls and professional meetings, which require the highest resolution images for display on large screens or where the capture of fine detail is essential.



### Key Features

- 4K Resolution with 300x zoom
- Supports HDMI, VGA, Ethernet, and USB output
- Shooting area (20.5" x 12.1") larger than A3
- Records to USB drives
- HDMI pass-through up to 4K resolution
- 5-year warranty\*



### Superior Image Quality

With a 4K camera and powerful zoom, the PS753 delivers remarkably detailed images to screens and projectors. The high-performance Sony sensor faithfully reproduces textures and colors in real-time, with excellent control over image noise.



### Wide Shooting Area

Lumens PS753 is extremely versatile, capable of reproducing documents and objects larger than A3 in size (over 20.5" x 12.1" / 50cm x 30cm). This gives presenters and demonstrators the flexibility that less powerful visualizers cannot match.

Where the operator needs a close-up shot, the 300x zoom can capture the finest detail. For maximum versatility, the ePTZ functionality changes the camera angle and position to focus on a specific part of the object. This gives you the precise image you need every time.



### Multi-Angle Lighting

The Lumens PS753 has dual lights on adjustable gooseneck mounts: any object is perfectly lit from above without glare or reflections. It also has a backlit LED light under the display area, making the visualizer ready to illuminate photo negatives and X-rays from below.



### Easy to Use

Despite its advanced features, Lumens PS753 is very easy to use. The Auto-Tune immediately calibrates the camera to deliver a perfectly focused image with accurate colors. The annotation tool allows the user to draw over the image on the screen without installing any additional software. It's fast, convenient, and simple to use. Use the included Ladibug software for advanced image control and connect to remote guests using your favorite conferencing platforms, such as Zoom, Meet, Skype, Teams, or WebEx.



### Fast Installation

The PS753 is very easy to install. Power is provided over your Ethernet network (PoE) without additional power supplies. The system can output live pictures over a connection that suits the way you work: it links directly to a display or projector over HDMI or VGA or streams images over your network.

# Applications



Higher Education



Courtroom




Medicine

## Product Specifications

Camera		Network	
Sensor	1/2.8" 8M CMOS	Ethernet	RJ-45 ( PoE+, IEEE802.3at)
Total Pixels	8.6 MP	IP Stream Format	RTSP(H.264 / AAC)
Total Zoom	300x (max.)	Storage	
Zoom	30x	Memory Slot	USB 2.0 Flash Drive, Expandable to 4TB
Digital Zoom	30x (max.)	Built-in Memory	100 JPEG
Output Resolution	XGA / 720p / 1080p / 2160p	Features	
Frame Rate	30 fps for all resolution 60fps for 1080p and 720p	Auto Tune	Yes, One Button for Optimization Image
Shooting Area Max.	522 x 308 mm (20.5" x 12.1")	Onboard annotation	Yes, Support USB Mouse
Sharpness	MTF 1700 Lines (at 2160p)	Image Mode	Photo / Text / Film / Slide / Microscope
Focus Mode	Auto / Manual	Freeze	Yes
Image Rotation	0° / 90° / 180° / 270° / Flip / Mirror	Pan	Yes
Lamp	1. Dual LED Side Lamps 2. Built-in A4 size (297 x 210 mm) LED Back-light	Picture in Picture (PIP)	Yes
Arm	Mechanical Arm	Mask / Spotlight	Yes
Input & Output		Lock Down Mode	Yes
Power Supplied	External, 12V DC Adapter (100~240 VAC) / PoE+	Auto Erase	Yes
Input	HDMIx1 (Support 4K), HDMI Pass-Through	Image Capture	Single or Continuous Capturing
Output	HDMI x1 / VGA x1 (up to 1080p) / USB 2.0 / IP Streaming	Standalone AV Recording	Yes, H.264 1080p
Control	RS-232 / USB / Ethernet	Ladibug™ Software	Support Windows 11, 10, 7 / Mac OS X / Chrome OS
USB		General	
USB Image Transmission	USB 2.0 (480 Mbps)	Anti-Theft	Kensington Anti-Theft Lock Device
Driver	UVC / UAC	VESA Mount	Yes, 75mm x 75mm
USB Host	USB 2.0 Type-A x1 (For Mouse, USB Flash Drive)	Power Consumption	DC In : 16W PoE : 18W
Audio		Dimensions: (WxHxD)	Folded : 22.3"x15.2"x6" (566x385x152 mm) Open : 18.3"x15.2"x23.1" (466x385x588 mm)
Built-in Microphone	Yes	Weight	12.3 lbs (5.6 kg)
Audio In	Built-in Mic, Line In (3.5mm)		
Audio Out	Line Out (3.5mm)		

## I/O Connections



**Lumens**®

Lumens Integration, Inc.  
4116 Clipper Court  
Fremont, CA, 94538  
Phone: +1-866-600-0988  
Fax: +1-510-252-1389

Lumens Europe  
De Nayerstraat 17 9470  
Denderleeuw Belgium  
Phone : +32-473-58-38-95  
Fax : +32-2-452-76-00



www.MyLumens.com